RTE. SECTION COUNTY TOTAL SHEET NO. 6734 05-00061-04-FP TAZEWELL 20 18 STA. TO STA. FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT Direction parallel to 89393 ∕-Tooth mark centerline General notes: ±20° 1. Coldmilling shall consist of two processes: Cutting with carbide teeth mounted on a rotating drum, and planing with a moldboard mounted immediately behind the cutting drum. 2. Other similar patterns will be acceptable if they consist of a smooth, flat, planed surface interspersed with a pattern of discontinuous longitudinal striations. В Area between tooth marks planed by moldboard ±0.5(0.02) PLAN Area cut by tooth 15(5/8) TO 20(3/4) Area planed by moldboard -Area planed by moldboard 350(14) R min.-DESIGNER NOTE
1. INCLUDE DISTRICT SPECIAL ±10(3/8) -Area cut by tooth 57(2.3) ±0.5(0.02) Existing bituminous surfacing left after cold milling Existing bituminous surfacing left after cold milling SECTION B-B PROJECTED PERPENDICULAR TO CENTERLINE All dimensions are in millimeters (inches) unless otherwise noted. ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT CADD STANDARD BITUMINOUS SURFACE REMOVAL (COLD MILLING) SECTION A-A CADD STD NO. 440001-D4

DGN-ONLY

1 01.dgn 2/22/2006 8:24:53 AW

440001-D4

DRAWN BY CADD

SCALE: NOT DRAWN TO SCALE

DATE \$\$DATE\$\$